

Data Structures and Fundamentals of Programming

Problem 1

In C++, implement the abstract data structure (ADT) queue as a **generic** class, called `Queue<T>`. Implement the queue using a **circular array**, it must use a **fixed sized array**. It will be generic on the type of the data to be stored. The implementation **must** utilize the entire fixed sized array in storing items. Give all class definitions and implement the following for `Queue`:

- Default constructor
- `push(T)` – takes a parameter of type `T` and adds it to the queue
- `T pop()` – removes a item from the queue
- `isEmpty()` – returns true when the queue is empty.
- `isFull()` – returns true when the queue is full.

You can **NOT** use STL or any other predefined library or built in types (such as `std::string`).

Problem 2

In C++ implement a *list/iterator* using a generic **double-linked-list** that uses dynamic memory allocation. The list must look like the following:

$$\text{beginning} \rightarrow X_0 \leftrightarrow X_2 \leftrightarrow \dots \leftrightarrow X_n \leftarrow \text{ending}$$

where X_0 is the first node in the list and X_n is the last node in the list. Besides the class called `List`, you will need class called `dnode`. Along with the class definition(s), you must implement the following methods, using standard semantics, for `List<T>`:

- `List()` - Default constructor
- `~List()` - Destructor
- `List(const List<T>&)` - Copy-constructor
- `insertAfter(const T&, Itr<T>)` – Adds an item after the node pointed to by the iterator.
- `remove(Itr<T>)` – removes the node pointed to by the iterator.
- `begin()` – returns an iterator to the front of the list
- `end()` – returns an iterator to the back of the list

Implement an iterator class called `Itr` for the `List` class. For the iterator you must write the following methods with standard semantics/behavior:

- `Itr()` - Default constructor
- `Itr(dnode<T>* ptr)` - constructor
- `operator++()` - pre-increment with standard semantics
- `operator++(int)` - post-increment with standard semantics

Note: Your implementation can NOT use STL or any other libraries (standard or otherwise).

Problem 3

In C++ implement a **binary search tree** abstract data type (ADT) that uses **dynamic memory allocation**. Make it a tree of integers. Along with the class definition(s), you must implement the following methods for the class:

- Default constructor
- Destructor – **must** be recursive or use a recursive method to delete the nodes.
- Copy-constructor – **must** be recursive or use a recursive method to copy the nodes.
- `insert` which takes a parameter of type integer and creates a new node that is added to the tree in the correct position based on the rules of a binary search tree.

Your implementation can **NOT** use STL or any other libraries (standard or otherwise).